

XOM 160



TECHNICAL SPECIFICATIONS

Engine	Type Displacement Max Power Torque Ignition	Liquid cooled, 4 Valve single cylinder SOHC 156 cc 10.9 kw (14.6 bhp) @ 8000 rpm 14 Nm @ 6500 rpm Fuel Injection (FI)
Transmission	Type Clutch Type	CVT Dry, Centrifugal
Suspension	Front Rear	Telescopic Hydraulic shock absorber Dual shock absorbers
Tyres	Front Rear	120/70 - 14 inch 140/60 - 14 inch
Dimensions	Length Width Height Wheelbase Seat Height Ground Clearance	1983 (mm) 772 (mm) 1214 (mm) 1348 (mm) 787 (mm) 155 (mm)
Electricals	Battery Starting System	12V- 6Ah /ETZ-7 Self
Weight	Kerb Weight Fuel Tank Capacity	142 kg 7 L

POWERFUL PERFORMANCE



LIQUID COOLED
ENGINE WITH 4 VALVE SINGLE
CYLINDER SOHC



i3s SILENT START
TECHNOLOGY

SUPERIOR GRIP



14 INCH LARGE WHEELS



BLOCK
PATTERN TYRES



REAR DUAL
SHOCK ABSORBERS

ENHANCED SAFETY



DUAL CHAMBER
LED HEADLAMP



FRONT DISC BRAKE
WITH ABS



LED
POSITION LAMP

CUTTING-EDGE TECHNOLOGY



SMART KEY WITH
REMOTE SEAT OPENING




DIGITAL SPEEDOMETER
WITH TURN-BY-TURN


COLOURS



MATTE
RAINFOREST GREEN



SUMMIT
WHITE



CANYON
RED



MATTE
VOLCANIC GREY

^Based on the testing report of Govt. certified agency. Actual mileage may vary as per riding conditions.