





UPGRADE TO ATTITUDE



Assist / Slipper Clutch

The assist slipper clutch, contributes to reducing the operating load of the clutch lever and a slipper function that reduces rear wheel hopping which results in a smoother and comfortable ride.



Single Cylinder DOHC Four Valve

Free-revving, and responsive, the single-cylinder DOHC four-valve engine pumps adrenaline at high rpm, with 20.3kW power. For improved control the six-speed gearbox gains an Assist/Slipper clutch.



LCD Meter with Gear Position Indicator

Full LED Lighting

beam, while the taillight is razor-thin.

The evocative round headlight uses a dual bar light

signature, upper for low beam and lower for high

The smart display includes engine rpm and fuel level as well as a negative-outline gear position indicator – so you always know what gear you're in.



Showa SFF-BP USD Forks

Upgraded the front suspension for precision handling ability; 41mm Showa Separate Fork Function Big Piston (SFF-BP) USD forks offer superb bump absorption and front-end feel.



IMU and ABS Braking Control

Two-channel ABS modulates the braking, dynamically managed by an Inertial Measurement Unit (IMU) to ensure brake force is evenly distributed between the front and rear wheels, minimizing rear wheel lift.







SPECIFICATIONS

ENGINE AND FUEL SYSTEM	
Engine Type	Liquid-cooled, 4 Stroke, DOHC, Single Cylinder
Displacement	250 cm ³
Bore x Stroke	76 mm x 55 mm
Compression Ratio	10.7: 1
Max. Power	20.3 kW @ 9,500 rpm
Max. Torque	23.4 N.m @ 7,750 rpm
Engine Oil Capacity	1.8 ℓ
Fuel System	Programmed Fuel Injection (PGM-FI)
TRANSMISSION	
Clutch Type	Manual Clutch Wet Multiplate Type
Transmission Type	Constant Mesh, 6 Speeds

Dilliensions (E X W X II)	2,020 Hilli X 000 Hilli X 1,000
Wheelbase	1,355 mm
Seat Height	800 mm
Ground Clearance	155 mm
Curb Weight	144 kg
Fuel Tank Capacity	10.1 ℓ
SUSPENSION	
Suspension Type	Front: 41mm Showa Separate Function Front Fork Big Piston (SFF-BP) USD Forks
	Monoshock Damper with 5 Stage Adjustable

DIMENSION AND WEIGHT

*Colours and photos may vary from the actual product.

WHEELS AND BRAKE	
Rim Size	Front: 17M/C x MT3.00
	Rear: 17M/C x MT4.00
Tyres	Front: 110/70R-17M/C 54H (Tubeless)
	Rear: 150/60R-17M/C 66H (Tubeless)
Brakes Type	Front: 296mm Hubless Floating Disc with Radial-mount Nissin 2-piston Calliper, ABS
	Rear: 220mm Hydraulic Single Disc with 1-piston Calliper, ABS
COLOUR VARIANT	

MAT GUN POWDER BLACK METALLIC

Honda BigBike

---- EXCITES THE WORLD -

All specifications are provisional and subject to change without notice.

- Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tyre pressure, installatio of accessories, cargo, rider and passenger
- These models come with a 2 year or 20.000km manufacturing warranty (whichever comes

[Toll Free Line 1800883993

https://hondabigbike.com.my

Honda Motorcycle Malaysia hondamotorcycle.my



012-499 3991

AUTHORISED DEALER STAMP

CANDY CHROMOSPHERE RED