

## MY24 NINJA ZX-6R BS6

Starting At Rs.11,20,000/- (Ex-Showroom)

### GET ON-ROAD PRICE

(<https://kawasaki-india.com/on-road-price-estimator/>)

\*Product pictures shown are for illustration purpose only.



### AVAILABLE COLOURS

● Metallic Graphite Gray / Metallic Diablo Black

● Lime Green / Ebony

\*Actual product may vary from the picture shown here.

\*Specification and pricing are subject to change.

### Engine & Transmission

TYPE	Liquid-cooled, 4-stroke In-Line Four
DISPLACEMENT	636 cm <sup>3</sup>
BORE AND STROKE	67.0 x 45.1 mm
COMPRESSION RATIO	12.9:1
VALVE SYSTEM	DOHC, 16 valves
FUEL SYSTEM	Fuel injection: ø38 mm x 4 with oval sub-throttles
FUEL TYPE / MINIMUM OCTANE RATING	-
IGNITION	Digital
STARTING	Electric
LUBRICATION	Forced lubrication, wet sump
TRANSMISSION	6-speed, return
MAXIMUM POWER	91.0 kW {124 PS} / 13,000 min-1
MAXIMUM POWER WITH RAM AIR	95.2 kW {129 PS} / 13,000 min-1
MAXIMUM TORQUE	69.0 N-m {7.0 kgf-m} / 11,000 min-1
ELECTRONIC RIDER AID	

### Dimensions & Chassis

FRAME TYPE	Perimeter, pressed-aluminium
RAKE / TRAIL	23.5o / 101 mm
TYRE - FRONT	120/70ZR17M/C (58W)
TYRE - REAR	180/55ZR17M/C (73W)

**Dimensions & Chassis**

WHEELBASE	1,400 mm
GROUND CLEARANCE	130 mm
SEAT HEIGHT	830 mm
CURB MASS	198 kg (EUR/AUS/S.E. Asia (B1/B3)/IDN/THA/PHL)
FUEL CAPACITY	17 litres
OVERALL DIMENSIONS (L X W X H)	2,025 X 710 X 1,105 mm

**Brakes & Suspension**

FRONT / WHEEL TRAVEL	ø41 inverted fork (SFF-BP) with rebound and compression damping and spring preload adjustability, and top-out springs
REAR / WHEEL TRAVEL	Bottom-Link Uni Trak, gas-charged shock with piggyback reservoir, compression and rebound damping and spring preload adjustability
BRAKE - FRONT	Dual semi-floating ø310 mm discs
CALIPER - FRONT	Dual radial-mount, monobloc, opposed 4-piston
BRAKE - REAR	Single ø220 mm disc
CALIPER - REAR	Single-bore pin-slide